

PRODUCT

Swatches



100  
WHITE  
OAK

Laminate  
Flooring



185  
DARK BROWN  
OAK

Laminate  
Flooring



300  
CLASSIC  
OAK

Laminate  
Flooring



500  
MONTANA BEIGE  
OAK

Laminate  
Flooring



510  
RUSTIC  
OAK

Laminate  
Flooring



530  
ELEGANT  
OAK

Laminate  
Flooring



550  
VINTAGE  
OAK

Laminate  
Flooring



570  
NATURAL  
OAK

Laminate  
Flooring



595  
OLD RIDGE  
OAK

Laminate  
Flooring



705  
GREY BRUSHED  
OAK

Laminate  
Flooring



710  
SILVER GREY  
OAK

Laminate  
Flooring



720  
SLATE GREY  
OAK

Laminate  
Flooring



AMOR CLASSIC LAMINATE FLOORING

Amor Classic not only harnesses the stylist nature of timber, these practical laminate planks also have a water resistance<sup>^</sup> surface meaning you won't need to worry about a spilled drink or muddy shoes on your floor. Create a modern looking interior space, with the peace of mind that your floor will stand up to everyday life.

<sup>^</sup>Subject to proper installation and maintenance.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed.

## PRODUCT

## Specifications

## AMOR CLASSIC - Product Details

## Technical Data

Type	Laminate	Colours	12
Plank Thickness	8mm	Country of Origin	Belgium
Dimensions	1200mm (L) x 190mm (W)	Finish	Matte
Planks per Box	7	Profile	Pressed Bevel
M <sup>2</sup> per Box	1.596m <sup>2</sup>	Surface	Embossed
M <sup>2</sup> per Pallet	95.76m <sup>2</sup>	Substrate Layer	850kg/m <sup>3</sup> High Density Fibreboard
Installation Method	Unifit®	Backing Layer	Balancing Layer



## Performance

Abrasion Rating	AC4	EN 13329
Classification	23, 32	ISO 10874
Light Fastness	Class 8 – Blue Reference	EN ISO 105-BO2
Static Indentation	≤0.05mm	EN433
Thickness Swelling	≤12%	ISO 24336
Impact Sound Reduction	Ln,W 55 IIC 54	ISO10140-3 ASTM E492-09
Flammability Rating	CRF 6.1 kW/m <sup>2</sup> Smoke Value 11%.min	AS/ISO 9239
Slip Resistance	P2	AS / NZ 4586-2013
Residential Warranty*	25 Year Residential Warranty 5 Year Water Resistance Warranty	
Commercial Warranty†	7 Year Commercial Warranty	

## Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits
------------	--

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Laminate products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Laminate Installation Instructions.

\*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Laminate Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst laminate products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.

Test results and certificates are available on request.